productinformation

tesa[®] 4174 Fine line tape for design painting

tesa[®] 4174 is a flexible, temperature resistant PVC fineline masking tape with a rubber adhesive for a wide range of design painting requirements

- no shrinking at high temperatures
- conforms to the dimensional change during oven-drying
- no edge lifting and can be removed without leaving any residues
- good conformability to multi dimensional surfaces

Main Application

- Lacquering work
- For masking of plastic parts and fine lines
- For sharp and flat paint edges
- For wide range of fineline applications

Technical Data

 Backing material Total thickness Type of adhesive Adhesion to steel Elongation at break 	PVC film 110 μm natural rubber 3.7 N/cm 200 %	 Tensile strength Temperature resistance Temperature resistance (PP-EPDM) Temperature resistance (paint) 	25 N/cm 150 °C 150 °C 150 °C
Properties			
 Hand tearability Easy to remove Suitable for die cutting Paint anchorage Sharp colour edge 	yes yes	Powerwash resistanceConformabilityFlame retardant	•••• ••• •••

Evaluation across relevant tesa[®] assortment: • • • • very good • • • good • • medium • low

Additional Information

tesa® 4174 is also available for converting and die-cutting with a paper liner (4174 PV4)

For latest information on this product please visit <u>http://l.tesa.com/?ip=04174</u>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

