
HALLMARK TAPES Ltd

Industrial Tape & Adhesive Distributor

Ashwell Street, Netherfield
Nottingham NG4 2FQ
Tel: 0115 987 0705
Fax: 0115 940 0082
Email: info@hallmarktapes.co.uk
Web: www.hallmarktapes.co.uk

PRODUCT DATA SHEET

Product Ref: Printed Laminated Tape

Description:

A single-sided, self-adhesive marking tape produced with a laminate of vinyl and clear polypropylene. Designed for interior use it provides long term performance as it is resistant to chemicals and the printed design is protected by a wipe-clean, scratch resistant coating.

It will adhere to most surfaces providing that they are clean and dust free.

Composition:

Backing :PVC film laminated with a clear polypropylene tape

Adhesive :Natural Rubber and hydrocarbon resin.

Properties:

Total Thickness : 0.095mm – 0.097mm

Peel Adhesion : 2.4 N/cm (+/- 0.5)

Storage: Tape performance is guaranteed within the first 12 months. Keep it in the original box and store in a dry atmosphere at temperature between 15°C and 25°C.

Statements, technical information and recommendations contained herein are based on production data with properties quoted being typical but intended only as a guide. They do not constitute a product specification nor are they to be construed in any manner as warranties expressed or implied. It is the responsibility of the purchaser to determine the suitability of the product for the application for which it is purchased, and to assume all risk and liability in connection therewith.

May 2008

